

SUSTAINABILITY DECLARATION



Item number
MO6351

Item description

Desk pen holder with 10W wireless charging phone stand and 2 USB ports for power charging.

Material content

Part	Component description	Position	Material	Weight Percentage
1	White plastic shell with grey printing	External	Acrylonitrile Butadiene Styrene (ABS)	58,59%
2	White plastic wire jacket	External	Polyvinyl Chloride (PVC)	7,44%
3	Coppery metal wire	Inside	Copper	5,80%
4	Semi-transparent adhesive tape	Inside	Acrylic acid	5,25%
5	Coppery metal wire	Inside	Copper	4,56%
6	Green PCB	Inside	Printed Circuit Board (PCB)	3,68%
7	White plastic jacket of plug	External	Polyvinyl Chloride (PVC)	1,67%
8	Grey soft plastic sheet	External	Silicon	1,58%
9	White plastic jacket of plug	External	Polyvinyl Chloride (PVC)	0,99%
10	Silvery metal shell of plug	Inside	Stainless Steel 304 - Carbon 0.05% - Silicon 0.3% - Manganese 1.74% - Phosphorus 0.036% - Sulfur 0.005% - Nickel 8.2% - Chromium 18.8% - Iron 70.869%	0,91%
11	Green PCB	Inside	Printed Circuit Board (PCB)	0,91%
12	Silvery metal screw	Inside	Aluminium alloy, Al,Be	0,84%
13	Silvery metal shell of plug	External	Stainless Steel 304 - Carbon 0.05% - Silicon 0.3% - Manganese 1.74% - Phosphorus 0.036% - Sulfur 0.005% - Nickel 8.2% - Chromium 18.8% - Iron 70.869%	0,68%
14	Black plastic wire covering	Inside	Polyvinyl Chloride (PVC)	0,68%
15	Green plastic wire covering	Inside	Polyvinyl Chloride (PVC)	0,68%
16	White plastic wire covering	Inside	Polyvinyl Chloride (PVC)	0,68%
17	Red plastic wire covering	Inside	Polyvinyl Chloride (PVC)	0,68%
18	Silvery metal pin of plug	External	Copper	0,53%
19	Black sponge sheet	Inside	Ethylene vinyl acetate copolymer	0,46%
20	Silvery metal screw	Inside	Aluminium alloy, Al,Be	0,46%
21	Silvery metal wire	Inside	Aluminium	0,46%
22	Black plastic core of plug	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,46%

23	Dark grey magnetic of inductor	Inside	Scale (coating), copper	0,30%
24	Grey soft plastic foot pad	External	Silicon	0,23%

Part	Component description	Position	Material	Weight Percentage
25	Silvery metal shell of socket	Inside	Stainless Steel 304 - Carbon 0.05% - Silicon 0.3% - Manganese 1.74% - Phosphorus 0.036% - Sulfur 0.005% - Nickel 8.2% - Chromium 18.8% - Iron 70.869%	0,23%
26	Silvery metal pin of plug	Inside	copper	0,15%
27	White plastic core of plug	External	Acrylonitrile Butadiene Styrene (ABS)	0,15%
28	Silvery metal shell of plug	Inside	Stainless Steel 304 - Carbon 0.05% - Silicon 0.3% - Manganese 1.74% - Phosphorus 0.036% - Sulfur 0.005% - Nickel 8.2% - Chromium 18.8% - Iron 70.869%	0,15%
29	Silvery metal pin of plug	Inside	copper	0,15%
30	Silvery metal screw	Inside	Aluminium alloy, Al,Be	0,08%
31	Black plastic core of plug	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,08%
32	Silvery metal pin of plug	Inside	copper	0,08%
33	Beige plastic shell of socket	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,08%
34	Beige plastic shell of socket	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,08%
35	Transparent glue	Inside	Acrylic acid	0,01%
36	Transparent plastic adhesive tape	Inside	POLIFILM K42	0,01%
37	White fibrous jacket	Inside	But-1-ene	0,01%
38	Beige glue	Inside	ethyl (((7S)-3,4-dimethoxybicyclo[4.2.0]octa-1,3,5-trien-7-yl)methyl)carbamate	0,01%
39	Dark grey magnetic sheet	Inside	Ferrite substances, magnetoplumbite-type, barium-cobalt-titanium	0,01%
40	White plastic wire covering	Inside	Polyvinyl Chloride (PVC)	0,01%
41	White plastic shell of plug	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,01%
42	Solder of plug	Inside	Tin alloy, dross	0,01%
43	Solder of plug	Inside	Tin alloy, dross	0,01%
44	Blue PCB of plug	Inside	Printed Circuit Board (PCB)	0,01%
45	Chip resistor	Inside	Beryllium	0,01%
46	Solder	Inside	Tin alloy, dross	0,01%
47	Solder	Inside	Tin alloy, dross	0,01%
48	Silvery metal pin of socket	Inside	copper	0,01%
49	Chip IC	Inside	IC	0,01%
50	Chip capacitor	Inside	alloy	0,01%
51	Chip IC	Inside	IC	0,01%
52	Chip inductor	Inside	Scale (coating), copper	0,01%
53	Chip LED	Inside	LED	0,01%
54	Chip capacitor	Inside	Alloy	0,01%
55	Chip resistor	Inside	Beryllium	0,01%
56	Chip diode	Inside	20% Silicon, 80% Gallium	0,01%
57	Silvery metal pin of socket	Inside	copper	0,01%
58	Black plastic shell of socket	Inside	Acrylonitrile Butadiene Styrene (ABS)	0,01%
59	Coppery metal wire	Inside	copper	0,01%
60	Silvery metal pin of socket	Inside	copper	0,01%
			Total	100,00%

Biodegradability of material	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
------------------------------	------------------------------	--

Recyclability of material	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
---------------------------	---	-----------------------------

Renewable source

Recycled material	Natural material	Reused waste material
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

End of life suggestion



Trademarks of material

-

Fulfilled technical standard

This item is compliant with the European legislation and regulations applicable to this item. A Declaration of Conformity (DOC) certificate and all relevant test reports are easily downloadable at our web shop.

Quality certifications/ social audits factory



Packaging and Transport

Piece	Inner Carton	Carton	no box	Polybag	Packaging
1	-	40	Y	-	-

We have dedicated partnerships with our carriers. Who have shown their commitments to reduce GHG emissions and have ambitious targets concerning carbon-neutral deliveries and climate-neutral logistics solutions.

midocean

Mrs. P. Varela



Buying & Portfolio Director